







SEMI-AUTOMATIC* Blowback; closed breech with floating firing pin Semi-Automatic only **MAGAZINES** Staggered box type holding 20, 25 or 32 rounds 9mm Parabellum for pistols **AMMUNITION** Firing selector in position "S" Fire selector in position "S" SAFETY SYSTEMS Fire selector in position "S" Pistol grip safety
Ratchet on Bolt-Retracting Slide Pistol grip safety 2. Pistol grip safety 3. Ratchet on Bolt-Retracting Slide Front: "Post" type Front: "Post" type Front: "Post" type SIGHTS Rear: L flip type Night Sight: Tritium (Beta) light Rear: L flip type Rear: L flip type adjustable for 100m (330 ft) adjustable for 100m (330 ft) and for 200m (660 ft). and for 200m (660 ft). Folding metal stock STOCK 260mm (10.2") 197mm (7.75") 410mm (16.1") OR 260mm (10.2") BARREL LENGTH LENGTH-STOCK FOLDED 470mm (18.4") 360mm (14.17") 620mm (24.4") OR 470mm (18.4") LENGTH-STOCK EXTENDED 650mm (25.6") 600mm (23.62") 800mm (31.5") OR 650mm (25.6") WEIGHT-UNLOADED 3.5kg (7.70 lbs) 2.70kg (5.94 lbs) 3.8kg (8.4 lbs) OR 3.5kg (7.7 lbs) 20-Round: 160g (5.6 oz) empty; 410g (14.4 oz) loaded MAGAZINE WEIGHTS[†] 25-Round: 200g (7.0 oz) empty; 490g (17.3 oz) loaded 32-Round: 220g (7.8 oz) empty; 600g (21.2 oz) loaded RIFLING 4 grooves (Right Hand Twist) - 1 turn in 254mm (10") MUZZLE VELOCITY[†] 420m/sec. 352m/sec. 380-460m/sec. (1377 ft/sec.) (1158 ft/sec.) (1250-1500 ft/sec.) Max. to 2000m (2200 yds) FIRING RANGET Max to 2000m (2200 yds) 150m (165 yds) at 30° elevation effective range at 30° elevation

950 rounds/min.

*Available with long (410mm or 16.1") or short (260mm or 10.2") barrel-see length and weight specifications.

600 rounds/min.

†Approximate depending on type of ammunition used.

RATE OF FIRE

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



Contact your distributor: